

IO-HTB1131-GLAN

USB Type-C Thunderbolt™ 3 to 10 Gigabit Network Adapter



• Feature

- Thunderbolt 3 interface with reversible USB-C connector
- Ethernet port supports auto-negotiation for 10Gb/s, 5Gb/s, 2.5Gb/s, 1Gb/s and 100Mb/s Base-T
- Bus powered 10GbE network adapter
- Jumbo frame support up to 16 KB
- 2.5W typical 10GBASE-T operating power per port: 100 meters of Cat 6A
- 1.5W typical 5GBASE-T operating power per port
- 1W typical 1GBASE-T operating power per port
- Audio Video Bridging (AVB) and PTP/1588v2
- Synchronous Ethernet (Sync-E), ITU-T standard in accordance with IEEE
- Supports Message-Signaled Interrupts (MSI and MSI-X), and legacy INTx PCIe interrupts
- Support for the Network Controller Sideband Interface (NC-SI)
- Management Component Transport Protocol (MCTP)
- IEEE 802.3an 10 Gbit/s Ethernet over unshielded twisted pair
- IEEE 802.3bz 2.5/5GBASE-T

CONTACT US

Address: Room 2302, Block A, Zhuoyue Merlin Center Plaza (South District), Meilin Road, Futian District, Shenzhen
Telephone: 0755-88851458

- IEEE 802.3ab 1000BASE-T Gigabit Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- IEEE 802.1Q VLANs
- IEEE 802.3x Full Duplex and flow contro
- IEEE 802.3az - Energy Efficient Ethernet (EEE)
- Support Preboot Execution Environment (PXE)
- FCoE No
- Operation Temperature :0°C to +108°C;
- Storage Temperature: -40°C to +110°C

• Specification

Chipset ID	AQC113
Number of Ports	1 Port
Transfer Rate	10000Mbps
Dimension	102.7*40.4*25.6mm
Environment	Operation Temperature :0°C to +108°C; Storage Temperature: -40°C to +110°C
OS Compatibility	Microsoft® Windows®,10,11 Linux Kernel, 3.10 and later releases MacOS

• Accessories

- 1 × Thunderbolt 10G Ethernet Adapter
- 1 × User Manual
- 1 × USB-C Cable

Note: Contents may vary depending on country/market

CONTACT US

Address: Room 2302, Block A, Zhuoyue Merlin Center Plaza (South District), Meilin Road, Futian District, Shenzhen
Telephone: 0755-88851458